


# SEMSS

Hexagon-nut, self-locking, DIN 985



**Galvanized, according to ISO 4042**

Product	Ø	t	SW	G
SEMSS 6	6 mm	6,00 mm	10 mm	0,20 kg/100
SEMSS 8	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10	10 mm	10,00 mm	17 mm	1,10 kg/100

**Stainless steel, according to ASTM 304 / BS 304 S 3**

Product	Ø	t	SW	G
SEMSS 6E	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 8E	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E	10 mm	10,00 mm	17 mm	1,10 kg/100

**Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11**

Product	Ø	t	SW	G
SEMSS 6E4	6 mm	6,00 mm	10 mm	0,20 kg/100
SEMSS 8E4	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E4	10 mm	10,00 mm	17 mm	1,00 kg/100

Ø : Diameter



**t** : Material thickness  
**SW** : Wrench size  
**G** : Weight

## DETAILS / APPLICATIONS

