


KHUSS 40

Support piece

The support piece is to be used in conjunction with KDU/KHU 40.



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	G
KHUSS 40S	0,11 kg

Incl.:	
1x SEM 10	Hexagon-nut, DIN 934
2x US 10X21	Square washer, DIN 125
1x SES 10X75	Hexagon head bolt, DIN 933

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	G
KHUSS 40F	0,11 kg

Incl.:	
1x SEM 10F	Hexagon-nut, DIN 934
2x US 10X21F	Square washer, DIN 125
1x SES 10X75F	Hexagon head bolt, DIN 933

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	G
KHUSS 40E	0,11 kg

Incl.:	
1x SEM 10E	Hexagon-nut, DIN 934
2x US 10X21E	Square washer, DIN 125
1x SES 10X75E	Hexagon head bolt, DIN 933





Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	G
KHUSS 40E4	0,11 kg
Incl.:	
1x SEM 10E4	Hexagon-nut, DIN 934
2x US 10X21E4	Square washer, DIN 125
1x SES 10X75E4	Hexagon head bolt, DIN 933

G : Weight



System E30 - E90. CNBOP-PIB nr CNBOP-PIB-KOT-2017/0013-3703

