


## WPLS 150

Wide-span inside riser, height=150 mm



Wide-span inside riser 90° for vertical change of direction, with integrated connectors. Formed components must be supported at all sides.

This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	R	G
WPLS 150-20F	150 mm	200 mm	450 mm	10,34 kg
Incl.: 8x KLS 10X20F			Fixing set	
WPLS 150-30F	150 mm	300 mm	450 mm	10,71 kg
Incl.: 8x KLS 10X20F			Fixing set	
WPLS 150-40F	150 mm	400 mm	450 mm	11,08 kg
Incl.: 8x KLS 10X20F			Fixing set	
WPLS 150-50F	150 mm	500 mm	450 mm	11,45 kg
Incl.: 8x KLS 10X20F			Fixing set	
WPLS 150-60F	150 mm	600 mm	450 mm	11,81 kg
Incl.: 8x KLS 10X20F			Fixing set	

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	R	G
WPLS 150-20E	150 mm	200 mm	450 mm	9,73 kg
Incl.: 8x KLS 10X20E			Fixing set	





Product	H	B	R	G
WPLS 150-30E	150 mm	300 mm	450 mm	10,07 kg
Incl.: 8x KLS 10X20E			Fixing set	
WPLS 150-40E	150 mm	400 mm	450 mm	10,42 kg
Incl.: 8x KLS 10X20E			Fixing set	
WPLS 150-50E	150 mm	500 mm	450 mm	10,76 kg
Incl.: 8x KLS 10X20E			Fixing set	
WPLS 150-60E	150 mm	600 mm	450 mm	11,11 kg
Incl.: 8x KLS 10X20E			Fixing set	

**H** : Height  
**B** : Width  
**R** : Radius  
**G** : Weight

## OPTIONAL ACCESSORIES



UL classified

