



LVB 60

Cable ladder vertical bend, height=60 mm

Cable ladder vertical bend for flexible vertical change of direction.
Riveted rungs.

This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	H	B	L	G
LVB 60-10S	60 mm	100 mm	350 mm	3,03 kg
LVB 60-20S	60 mm	200 mm	350 mm	3,21 kg
LVB 60-30S	60 mm	300 mm	350 mm	3,39 kg
LVB 60-40S	60 mm	400 mm	350 mm	3,56 kg
LVB 60-50S	60 mm	500 mm	350 mm	3,74 kg
LVB 60-60S	60 mm	600 mm	350 mm	3,91 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	G
LVB 60-10F	60 mm	100 mm	350 mm	3,46 kg
LVB 60-20F	60 mm	200 mm	350 mm	3,65 kg
LVB 60-30F	60 mm	300 mm	350 mm	3,85 kg
LVB 60-40F	60 mm	400 mm	350 mm	4,05 kg
LVB 60-50F	60 mm	500 mm	350 mm	4,24 kg
LVB 60-60F	60 mm	600 mm	350 mm	4,44 kg





Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	L	G
LVB 60-10E	60 mm	100 mm	350 mm	3,03 kg
LVB 60-20E	60 mm	200 mm	350 mm	3,21 kg
LVB 60-30E	60 mm	300 mm	350 mm	3,39 kg
LVB 60-40E	60 mm	400 mm	350 mm	3,56 kg
LVB 60-50E	60 mm	500 mm	350 mm	3,74 kg
LVB 60-60E	60 mm	600 mm	350 mm	3,91 kg

- H** : Height
- B** : Width
- L** : Length
- G** : Weight



System E30 - E90. CNBOP-PIB nr CNBOP-PIB-KOT-2017/0013-3703

