



HS22

Śruba z łbem młoteczkowym, A 2/ A 4

Ocynk galwaniczny, zgodnie z ISO 4042

Produkt	L	Ø	G
HS22 12X30	30 mm	12 mm	9,50 kg/100
HS22 12X40	40 mm	12 mm	10,0 kg/100
HS22 12X50	50 mm	12 mm	10,8 kg/100
HS22 12X60	60 mm	12 mm	11,40 kg/100
HS22 16X40	40 mm	16 mm	16,20 kg/100
HS22 16X60	60 mm	16 mm	18,60 kg/100

Ocynk zanurzeniowo-ogniowy, zgodnie z BS 729 (DIN EN ISO 1461)

Produkt	L	Ø	G
HS22 10X80F	80 mm	10 mm	9,70 kg/100

Stal kwasoodporna, zgodnie z ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Produkt	L	Ø	G
HS22 10X80E4	80 mm	10 mm	9,70 kg/100
HS22 12X30E4	30 mm	12 mm	9,60 kg/100
HS22 12X40E4	40 mm	12 mm	10,10 kg/100
HS22 12X50E4	50 mm	12 mm	10,90 kg/100
HS22 12X60E4	60 mm	12 mm	11,50 kg/100
HS22 16X40E4	40 mm	16 mm	16,30 kg/100
HS22 16X60E4	60 mm	16 mm	18,70 kg/100

Strona 1



L : Długość
Ø : Średnica
G : Waga

DETALE / ZASTOSOWANIE

