

FRSV

Round-head screw with short square, DIN 603



Galvanized, according to ISO 4042

Product	L	Ø	d	G
FRSV 6X12	12 mm	6 mm	1,50 mm	0,50 kg/100
FRSV 6X16	16 mm	6 mm	1,50 mm	0,70 kg/100
FRSV 8X16	16 mm	8 mm	2,00 mm	1,30 kg/100
FRSV 10X20	20 mm	10 mm	2,50 mm	2,30 kg/100

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	Ø	d	G
FRSV 10X20F	20 mm	10 mm	2,50 mm	2,30 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	Ø	d	G
FRSV 6X12E	12 mm	6 mm	1,50 mm	0,50 kg/100
FRSV 6X16E	16 mm	6 mm	1,50 mm	0,70 kg/100
FRSV 8X16E	16 mm	8 mm	2,00 mm	1,30 kg/100
FRSV 10X20E	20 mm	10 mm	2,50 mm	2,30 kg/100




Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	L	Ø	d	G
FRSV 6X12E4	12 mm	6 mm	1,50 mm	0,50 kg/100
FRSV 10X20E4	20 mm	10 mm	2,50 mm	2,40 kg/100

L : Length
Ø : Diameter
d : Thickness
G : Weight

DETAILS / APPLICATIONS



System E30 - E90. CNBOP-PIB nr CNBOP-PIB-KOT-2017/0013-3703

