


FR
Spring ring

Spring ring.



Galvanized, according to ISO 4042

Product	D	Ø	G
FR B6	11,8 mm	6,1 mm	0,10 kg/100
FR B8	14,8 mm	8,1 mm	0,15 kg/100
FR B10	18,1 mm	10,2 mm	0,20 kg/100
FR B12	21,1 mm	12,2 mm	0,25 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	D	Ø	G
FR B6E	11,8 mm	6,1 mm	0,10 kg/100
FR B8E	14,8 mm	8,1 mm	0,15 kg/100
FR B10E	18,1 mm	10,2 mm	0,20 kg/100
FR B12E	21,1 mm	12,2 mm	0,25 kg/100

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	D	Ø	G
FR B6E4	11,8 mm	6,1 mm	0,10 kg/100
FR B8E4	14,8 mm	8,1 mm	0,15 kg/100
FR B10E4	18,1 mm	10,2 mm	0,20 kg/100
FR B12E4	21,1 mm	12,2 mm	0,25 kg/100



D : Diameter
Ø : Diameter
G : Weight

DETAILS / APPLICATIONS

