


## SEMSS

Nakrętka sześciokątna, samozabezpieczająca, DIN 985



### Cynkowanie galwaniczne, EN ISO 4042

Produkt	Ø	t	SW	G
SEMSS 6	6 mm	6,00 mm	10 mm	0,20 kg/100
SEMSS 8	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10	10 mm	10,00 mm	17 mm	1,10 kg/100

### Stal nierdzewna, zgodnie z ASTM 304 / BS 304 S 3

Produkt	Ø	t	SW	G
SEMSS 6E	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 8E	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E	10 mm	10,00 mm	17 mm	1,10 kg/100

### Stal kwasoodporna, zgodnie z ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Produkt	Ø	t	SW	G
SEMSS 6E4	6 mm	6,00 mm	10 mm	0,20 kg/100
SEMSS 8E4	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E4	10 mm	10,00 mm	17 mm	1,00 kg/100

Ø : Średnica

Strona 1



**t** : Grubość materiału  
**SW** : Rozmiar klucza  
**G** : Waga

## DETALE / ZASTOSOWANIE

