



WPV 100

Wide-span coupler, height=100 mm

In order to compensate for the heat expansion one side of the connector is mounted as a loose bearing. The given torque must be observed. The other side of the connector is to be mounted as a fixed bearing. A minimum distance of 4 mm must be kept between the cable ladders.

This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	H	L	G
WPV 100S	100 mm	400 mm	0,99 kg
Incl.:			
4x KLS 10X20 4x FRSV 10X20 4x US 10X21 4x SEMSS 10		Fixing set Round-head screw with short square Square washer, DIN 125 Hexagon-nut, self-locking, DIN 985	

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	L	G
WPV 100F	100 mm	400 mm	1,06 kg
Incl.:			
4x KLS 10X20F 4x FRSV 10X20F 4x US 10X21F 4x SEMSS 10E		Fixing set Round-head screw with short square Square washer, DIN 125 Hexagon-nut, self-locking, DIN 985	

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	L	G
WPV 100E	100 mm	400 mm	0,99 kg
Incl.:			
4x KLS 10X20E 4x FRSV 10X20E 4x US 10X21E 4x SEMSS 10E		Fixing set Round-head screw with short square Square washer, DIN 125 Hexagon-nut, self-locking, DIN 985	





H : Height

L : Length

G : Weight

