


WPDUK

Cover clamp



Cover clamp with screw head for mounting wide span covers on the underside for a flat appearance.

Can also be used as storm protection angle. According to assembly instructions you should use at least 6 safety elements for each 3 meters cable path cover. For wind-exposed areas, the number of cover clamps must be increased to at least 10 pcs.

Cover clamp can be use with system WPR and WPL.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	t	M	G
WPDUK F	22 mm	20 mm	21 mm	3,00 mm	2,0 Nm	0,02 kg

Incl.:						
1x SES 6X20E	Hexagon head bolt, DIN 933					

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	L	t	M	G
WPDUK E	22 mm	20 mm	21 mm	3,00 mm	2,0 Nm	0,02 kg

Incl.:						
1x SES 6X20E	Hexagon head bolt, DIN 933					

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	L	t	M	G
WPDUK E	22 mm	20 mm	21 mm	3,00 mm	2,0 Nm	0,02 kg

Incl.:						
1x SES 6X20E	Hexagon head bolt, DIN 933					



H : Height
B : Width
L : Length
t : Material thickness
M : Torque
G : Weight

DETAILS / APPLICATIONS

