



WPFDK

Fitting cover hook clip

Can also be used as storm protection angle. The number of cover brackets depends on the number of holes drilled in moulded cover.

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	G
WPFDK 100E	100 mm	0,07 kg
Incl.:		
2x US 8X17E 1x SEM 8E	Square washer, DIN 125 Hexagon-nut, DIN 934	
WPFDK 120E	120 mm	0,08 kg
Incl.:		
2x US 8X17E 1x SEM 8E	Square washer, DIN 125 Hexagon-nut, DIN 934	
WPFDK 150E	150 mm	0,09 kg
Incl.:		
2x US 8X17E 1x SEM 8E	Square washer, DIN 125 Hexagon-nut, DIN 934	

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	L	G
WPFDK 100E4	100 mm	0,07 kg
Incl.:		
2x US 8X17E4 1x SEM 8E	Square washer, DIN 125 Hexagon-nut, DIN 934	
WPFDK 120E4	120 mm	0,08 kg
Incl.:		
2x US 8X17E4 1x SEM 8E4	Square washer, DIN 125 Hexagon-nut, DIN 934	



PRODUCT INFORMATION



Product	L	G
WPFDK 150E4	150 mm	0,09 kg

Incl.:		
2x US 8X17E4 1x SEM 8E4	Square washer, DIN 125 Hexagon-nut, DIN 934	

L : Length

G : Weight

